

PRECISION SPRAY ASPHALT DISTRIBUTOR

- Automatic, Heated Clean-Out System
- Heated Asphalt Pump and Heated Solvent Tank
- 8-16 ft. Telescoping Spray Bar, Vertical Extensions to 24 ft.
- Internal Poppet Spray Valves
- Dual, Diesel Fired Burners with Auto-Thermostat Control
- 1000 3500 Gallon Truck Mounted Tanks
- Truck Mounted, Roll-On/Roll-Off, Trailer Mounted and Slip-in Units Available



Precision Spray - Fully Automatic Aspha



The Precision Spray is leading the way in asphalt distributor innovation and technology. Companies nation wide are seeking a machine that is simple and easy to run and maybe more importantly, simple and easy to maintain.

Telescoping Spraybar

Standard 8-16 ft. telescoping bar is the preferred bar by many material specialists. Production and ease of operation are at the core of its qualities.

Asphalt Pump

High quality, high volume, heated 400 GPM asphalt pumps are found on every Precision Spray distributor. The pump center-line is located at the sump level of the tank for maximum performance.

Double Flue Design

CBC engineering has incorporated a standard double flue design technology. This design is located very low in the tank to permit minimum start-up times, even at low tank levels. Maximum tube heating area and standard diesel burners yield short heating cycles.

Automatic Clean-Out Cyle

Leading the way in design technology is the Precision Spray's exclusive heated, automatic clean-out cycle. Never has clean-up been so easy and simple. Clean-out that is done 100% of the time, accurately and without question. Simply turn master control to "Clean-Out" and press "Start."

Master and Cab Controls

Safety first. This can be illustrated in the fact that whenever the master control is active, the cab control is completely inactive. No accidents by cab operator while performing various operations at the master control. Redundant cab control wiring harness and easy computer programmability translates into uptime.





lt Distributor





Masters of the Mat





Load material using the Precision Spray 400 GPM asphalt pump. All pump functions pass through a single, self-cleaning strainer.



Precision Spray's exclusive center breakaway system allows the bar to move if hit by an object.



Easy access to the heated asphalt pump & control valves make the Precision Spray very service friendly.

Calder Brothers Corporation is a leading manufacturer in asphalt related products including commercial pavers, asphalt rollers, tack-coat sprayers, maintainers, motor graders, water trucks and asphalt distributors. Building a quality product based on sound engineering practices and using field tested, time proven components is our focus.

CBC demands performance and reliability out of each machine we manufacture. These same demands are expected from our partners as well, helping us insure quality product with unmatched service and support.

PRECISION SPRAY ASPHALT DISTRIBUTOR

TANK CONSTRUCTIO	IANK CONSTRUCTION - meets all applicable Federal Cargo Tank Regulations 49 CFR 173.247	SPRAYBAR	
Tank Shell	10 gauge Steel, Oval in Shape	Type	8' to 16' Telescoping with Straight-Line Start and Stop
Heads	7 gauge Steel, Dished and Flanged		Automatic, Fully Circulating
Surge Plate(s)	7 gauge Steel, Dished and Flanged	Extensions	1', 2' and 4' Available, Vertically Foldding
Manhole	20" Diameter with Curbside Ladder Access and Spill Collar	Breakaway	Center, Mechanical Breakaway System
Tank Insulation	2" Mineral Wool on Front Head and Sides	Spray Valves	Internal Poppet, No Leak Design on 4" Centers
	4" Mineral Wool on Rear Head		Air Operated with Spring Assit
Tank Skin	0.050" Aluminum Jacket	Cross Section	12 cubic inch High Volume
Overflow	3" Internal	Spray Width Control	Electric/Hydraulic with 4" Control
Contents Gauges	Front and Rear, Float Type, 100 gallon Increments	Spray Height Control	Electric/Hydraulic with Safety Chains
Sampling Valve	Located on Front Head	Travel Lock	Mechanical
Capacities	1000 to 3500 gallon Truck Mounted or Roll-On/Roll-Off	ELLIQUICI EAN OUT SYSTEM	20070
ACDUAL T DIMO		Tuno Tuno	Eully Automotic with Duch Button Chat
Туре	Positive Displacement Rotary Gear Type		Self Contained, Environmentally Friendly
Flow	400 GPM	Solvent Tank	25+ gallon, Heated
Heat	Fully Heat Jacket Asphalt Pump	Components Cleaned	Asphalt Pump, Strainer Box, All Plumbing,
Location	Pump Centerline Below Bottom Level of Tank Sump		Entire Spraybar, All Valves
Stainer System	Single Location, Auto-Cleaing, Quick-Change	Pre-Soak/Washdown	Air Operated, 15' Hose, Atomizes Solvent
	All Function Protection	00000 000000 0000000000000000000000000	
		CONTROLS	
HEATING SYSTEM		Master Controls	Located Rear Curbside, Pump Speed, Pump Direction, Load,
Flues	Two Flue Tubes with Stainless Steel Liners		Unload, Transfer, Tank Circulate, Hand Spay, Clean-Out,
Burners	Two, Diesel Fired with 25 gallon Tank		Burners On/Off, Cab Controls On/Off
Temperature Control	Automatic, Thermostatically Controlled	Cab Controls	Spray On/Off, Application Rate, Spray Width, Spray Distance,
	4" Dial and Pencil Thermometers		Pump Calibration, Travel Calibration, Application Rate Presets
Safety	Out-Fire Protection and Low Level Ignite Protection		
Controls	Blowers and Fuel on Separate Switches	OTHER STANDARD EQUIPMI	EQUIPMENT
Exhaust Stacks	Two, Rear Mounted, Insulated	Single Nozzle Hand Spra	Single Nozzle Hand Spray Attachment with 25' Hose, LED Lights, Redundant Wire
	14 gauge Stainless Construction	Harness between Master and Cab	and Cab Controls, 8' Spray Curtain, Diamond Plate Fenders

Sold & Serviced by:



