



### Specs for MC900:

|                                       |  |
|---------------------------------------|--|
| Operating Weight                      | 959 lb.  |
| Height (steering handle down)         | 40.5"  |
| Width                                 | 32.25"   |
| Length with Form (steering handle up) | 91.5"  |
| Wheelbase                             | 71"  |
| Hopper Capacity                       | 9.0 cubic feet   |
| Standard Tire Configuration           | (4) 4.10 x 3.50 pneumatic front +<br>(3) 8" dia. X 2.5" sold rubber rear   |
| Engines                               | 20.3 HP Honda  |
| Engine Starting System                | Electric   |
| Fuel Capacity                         | 3.3 gallon   |
| Standard Auger Configuration          | (3) cast 6" dia. X 9" lg.  |
| Optional Auger Configurations         | (3) cast 5" dia. X 9" lg.<br>(3) welded 8" dia. X 9" lg.<br>(3) welded 10" dia. X 9" lg.   |
| Hollow Auger Shaft (to extrude rebar) | Not Available  |
| Drive System                          | Automatic centrifugal clutch to enclosed 8:1 gear<br>reducer; final auger drive chain & sprocket<br>Extrusion process provides self-propulsion |
| Steering                              | Tie rod with 40" steering handle   |
| Brake                                 | Friction pad on steering handle  |